


## XS/XM 24V ELECTRONIC LIFT TRUCKS

Ideal for light handling of goods on pallets in medium/small warehouses.



The trucks are fitted with a shock absorber system that ensures perfect contact of the driving wheel with the floor, even in the case of deep bumps.



XS

XM

### STANDARD EQUIPMENT

- High-frequency electronic plant 24V with microprocessor fault research, technology without mechanical working relay
- Electronic battery charger 24V 15A with microprocessor (XS)
- Electronic battery charger 24V 20A with microprocessor (XM)
- N.2 12V 100 Ah armoured traction batteries with tubular plates (XS)
- N.2 12V 155 Ah armoured traction batteries with tubular plates (XM)
- Fixed forks long mm. 1150
- 200 mm. free lift (XM)
- Ignition lock key
- Push-button forks controls
- Electric limit switch (XM)
- Braking in release contraflow
- Electromagnetic parking brake
- Shock absorber on driving-wheel
- Chromed oleodynamic piston
- Emergency push-button
- Safety push-button for accident prevention
- Automatic speed reduction (XM)
- Manual release of traction group
- Acoustic warning signal
- Battery discharged warning indicator
- Shock resistant ergonomic steering rudder

model		XS 1016	XM 1029
Q	kg	1000	1000
C	mm	600	600
I	mm	1150	1150
L	mm	1780	1935
X	mm	380	415
X2	mm	205	175
Y	mm	1195	1345
L2	mm	630	780
M	mm	530	530
N	mm	160	160
b1	mm	1990	1990
b2	mm	1470	200
b3	mm	1600	2900
b4	mm	2115	3420
B	mm	800	840
WA	mm	1430	1530





Diagram representing the positive variation of the load baricenter with the variation of the space.

INOX  
AVAILABLE

